

FrameMaker-to-Acrobat TimeSavers Shortcuts v. 5.0 (inserted in hypertext markers) (1 of 7)

| Shortcut | Function | Item defined | Hypertext marker syntax | Notes |
|---------------------------------|----------------------------------|--------------|--|--|
| Common Acrobat Functions | | | | |
| ~SearchLink | Open Acrobat's Search dialog box | Link | alert ~SearchLink | All Acrobat/Reader versions (appropriate version-specific command issued through Acrobat JavaScript) |
| ~SearchBmk | | Bookmark | alert ~SearchBmk (Bookmark Title) /CS | Pre-defined searches (through bookmarks, popup menus) can be specified with the Navigation Assistant (TimeSavers add-on) |
| ~Search5Link | Open Acrobat 5 Search dialog box | Link | alert ~Search5Link | Acrobat/Reader versions prior to 8 |
| ~Search5Bmk | | Bookmark | alert ~Search5Bmk (Bookmark Title) /CS | Acrobat/Reader versions prior to 8 |
| ~Search8Link | Open Acrobat 8 Search dialog box | Link | alert ~Search8Link | Acrobat/Reader 8 specific |
| ~Search8Bmk | | Bookmark | alert ~Search8Bmk (Bookmark Title) /CS | Acrobat/Reader 8 specific |
| ~FindLink | Open Acrobat's Find dialog box | Link | alert ~FindLink | |
| ~FindBmk | | Bookmark | alert ~FindBmk (Bookmark Title) /CS | |
| ~PrintLink | Open Acrobat's Print dialog box | Link | alert ~PrintLink | |
| ~PrintBmk | | Bookmark | alert ~PrintBmk (Bookmark Title) /CS | |
| ~CloseLink | Close current PDF document | Link | alert ~CloseLink | |
| ~CloseBmk | | Bookmark | alert ~CloseBmk (Bookmark Title) /CS | |
| ~ExitLink | Quit Acrobat/Reader | Link | alert ~ExitLink | |
| ~ExitBmk | | Bookmark | alert ~ExitBmk (Bookmark Title) /CS | |

Notes:

- All shortcuts can reference text or file items contained in the TimeSavers text library (TS-custom.ini)
- Where the syntax includes /CS, this means a 2-letter control string, where C=color label, S=font style (0=regular, 1=italic, 2=bold, 3=bold italic).

FrameMaker-to-Acrobat TimeSavers Shortcuts v. 5.0 (inserted in hypertext markers) (2 of 7)

| Shortcut | Function | Item defined | Hypertext marker syntax | Notes |
|--------------------|--|--------------|---|---|
| Web-Related | | | | |
| ~MailtoLink | Create a link or a bookmark to an e-mail address, automatically filtering spaces and other special characters to the required hex characters | Link | alert ~MailtoLink (recipient@domain.com ?Subject=Suggest a new feature ?Body=Ego ille quem nosti apros et quidem pulcherrimos cepi) | |
| ~MailtoBmk | | Bookmark | alert ~MailtoBmk (Bookmark Title) /CS (xyz@abc.com?Subject=nnn?Body=ddd) | |
| ~httpLink | Create a link or a bookmark pointing to a web site | Link | alert ~httpLink (WebAddr) | Web address is automatically prefixed with http:// |
| ~httpBmk | | Bookmark | alert ~httpBmk (visit web page) /CS (WebAddr) | |
| ~httpsLink | Create a link or a bookmark pointing to a secured web site | Link | alert ~httpsLink (WebAddr) | Web address is automatically prefixed with https:// |
| ~httpsBmk | | Bookmark | alert ~httpsBmk (visit web page) /CS (WebAddr) | |
| ~ftpLink | Create a link or a bookmark pointing to an ftp site | Link | alert ~ftpLink (ftpAddr) | Address is automatically prefixed with ftp:// |
| ~ftpBmk | | Bookmark | alert ~ftpBmk (visit web page) /CS (ftpAddr) | |
| ~NewWinHttpLink | Create a link or a bookmark pointing to a web site, opening a new browser window | Link | alert ~NewWinHttpLink (WebAddr) | Web address is automatically prefixed with http:// |
| ~NewWinHttpBmk | | Bookmark | alert ~NewWinHttpBmk (visit web page) /CS (WebAddr) | |
| ~NewWinFtpLink | Create a link or a bookmark pointing to an ftp site, opening a new browser window | Link | alert ~NewWinFtpLink (ftpAddr) | Address is automatically prefixed with ftp:// |
| ~NewWinFtpBmk | | Bookmark | alert ~NewWinFtpBmk (visit web page) /CS (ftpAddr) | |

FrameMaker-to-Acrobat TimeSavers Shortcuts v. 5.0 (inserted in hypertext markers) (3 of 7)

| Shortcut | Function | Item defined | Hypertext marker syntax | Notes | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|---|--|---|---|--|------------------------|--|---|-------------------------|-----------------------------------|-----------------|-------------|--------------|--|------------------|------------|----------|-----------------|--|-------------------------|------------|---------|-----------------|--|--|-------------------|---------------|---------------|--|--|-------------------|---------------|------------------|--|--|-------------------|----------|------------------|--|--|---------------|--------------|-------------------------------------|--|--|-----------|--|--|--|--|
| Annotations | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| ~Note | Define Acrobat notes with full control over title, icon, dimensions, location, color, open/close state | Annotation | alert ~note /TLCO (Note Title) (Contents) | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| <p>/TLCO is a 4-letter control string, where:</p> <table> <tr> <td>T is icon type:</td> <td></td> <td>L is note location relative to the hypertext marker's active area:</td> <td>C is color label</td> <td>O is note's initial state:</td> </tr> <tr> <td>a = right arrow</td> <td>c = comment</td> <td>1 = top left</td> <td></td> <td>Y (or y) = open,</td> </tr> <tr> <td>e = circle</td> <td>h = help</td> <td>2 = middle left</td> <td></td> <td>else closed (icon only)</td> </tr> <tr> <td>i = insert</td> <td>k = key</td> <td>3 = bottom left</td> <td></td> <td></td> </tr> <tr> <td>l = up left arrow</td> <td>m = checkmark</td> <td>4 = top right</td> <td></td> <td></td> </tr> <tr> <td>n = new paragraph</td> <td>p = paragraph</td> <td>5 = middle right</td> <td></td> <td></td> </tr> <tr> <td>r = right pointer</td> <td>s = star</td> <td>6 = bottom right</td> <td></td> <td></td> </tr> <tr> <td>t = text note</td> <td>u = up arrow</td> <td>(default note dimensions: 2.7×2.7")</td> <td></td> <td></td> </tr> <tr> <td>x = cross</td> <td></td> <td></td> <td></td> <td></td> </tr> </table> | | | | | T is icon type: | | L is note location relative to the hypertext marker's active area: | C is color label | O is note's initial state: | a = right arrow | c = comment | 1 = top left | | Y (or y) = open, | e = circle | h = help | 2 = middle left | | else closed (icon only) | i = insert | k = key | 3 = bottom left | | | l = up left arrow | m = checkmark | 4 = top right | | | n = new paragraph | p = paragraph | 5 = middle right | | | r = right pointer | s = star | 6 = bottom right | | | t = text note | u = up arrow | (default note dimensions: 2.7×2.7") | | | x = cross | | | | |
| T is icon type: | | L is note location relative to the hypertext marker's active area: | C is color label | O is note's initial state: | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| a = right arrow | c = comment | 1 = top left | | Y (or y) = open, | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| e = circle | h = help | 2 = middle left | | else closed (icon only) | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| i = insert | k = key | 3 = bottom left | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| l = up left arrow | m = checkmark | 4 = top right | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| n = new paragraph | p = paragraph | 5 = middle right | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| r = right pointer | s = star | 6 = bottom right | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| t = text note | u = up arrow | (default note dimensions: 2.7×2.7") | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| x = cross | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| ~RevBmk | Define a bookmark to a specific location, place a revision mark in that location | Bookmark + revision mark | alert ~RevBmk (SRC:my comment...) n /CS | The revision mark character (printable) is the first character in the text string, formatted using the Dingbats font, with the same color as the bookmark. n = horizontal offset from left (-1 for marker's horizontal location) | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| ~ClickMsg | | Message box | alert ~ClickMsg (message) | Lets you define an Acrobat pop-up, which may be used for glossary definitions. | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| ~ClickMsgT | | Titled message box (Acrobat 6 or higher) | alert ~ClickMsgT (title) (text) | When a link defined this way is activated in Acrobat/Reader 5, the title is not displayed (instead, the standard "Adobe Acrobat" title is displayed). The message itself, however, is displayed the same way in Acrobat/Reader 5 or higher versions. | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |

FrameMaker-to-Acrobat TimeSavers Shortcuts v. 5.0 (inserted in hypertext markers) (4 of 7)

| Shortcut | Function | Item defined | Hypertext marker syntax | Notes |
|----------------------------|--|--------------|---|--|
| External References | | | | |
| ~FileLink | Activate a data file | Link | alert ~FileLink (file.ext) | The~HelpLink and alert ~HelpBmk custom shortcuts create direct links/bookmarks to topics in WinHelp files. |
| ~FileBmk | | Bookmark | alert ~FileBmk (Bookmark Title) /CS (filename.ext) | |
| ~PdfLink | Open the target PDF | Link | alert ~PdfLink (filename) | Type only the file name, enclosed in parentheses, without the extension (.pdf extension added automatically) |
| ~PdfBmk | | Bookmark | alert ~PDFBmk (Bookmark Title) /CS (filename) | |
| ~PdfNewWinLink | Open the target PDF in a new window | Link | alert ~PdfNewWinLink (filename) | |
| ~PdfNewWinBmk | | Bookmark | alert ~PdfNewWinBmk (Bookmark Title) /CS (filename) | |
| ~PdfPageLink | Open the target PDF at the specified page, in a new window | Link | alert ~PdfPageLink (filename) num | |
| ~MovieLink | Create a link to a movie file | Link | alert ~MovieLink (MovieTitle) (filename.ext) | |
| ~MovieFloatLink | Create a link to a movie file in a floating window | Link | alert ~MovieFloatLink (MovieTitle) (filename.ext) | |
| ~MovieURLLink | Create a link to a web-based movie file (floating window) | Link | alert ~MovieURLLink (MovieTitle) (www.microtype.com/sample.mov) | Web address is automatically prefixed with http:// |
| ~MovieBmk | Create a bookmark to a movie file, pre-defined by a ~Movie link shortcut, by its title | Bookmark | alert ~MovieBmk (Bookmark Text) /CS (MovieTitle) | |

FrameMaker-to-Acrobat TimeSavers Shortcuts v. 5.0 (inserted in hypertext markers) (5 of 7)

| Shortcut | Function | Item defined | Hypertext marker syntax | Notes |
|-------------------|--|--------------|-------------------------|--|
| Navigation | | | | |
| ~PageGoToLink | Create clickable page numbers in Acrobat, opening Acrobat's Go To Page dialog box | Link | alert ~PageGoToLink | |
| ~PageFirstLink | Create a link to the first page in the PDF file, even when it is a multi-chapter PDF (entire book converted to a single PDF file) | Link | alert ~PageFirstLink | FrameMaker's built-in <code>gotolink firstpage</code> hypertext marker creates a link to page 1 in the current PDF. When a FrameMaker book is converted to a single PDF, the resulting link points to the first page of each chapter. |
| ~PageLastLink | Create a link to the last page in the PDF file (regardless of its page number), even if it is a multi-chapter PDF (entire book converted to a single PDF file) | Link | alert ~PageLastLink | FrameMaker's built-in <code>gotolink lastpage</code> creates a link to the last page in the current PDF by its page number. If pages are added or deleted manually in the PDF file, the link becomes invalid. When a FrameMaker book is converted to a single PDF, the resulting link points to the last page of each chapter. |
| ~PageNextLink | Create a link which displays the <i>top</i> of the next page | Link | alert ~PageNextLink | FrameMaker's built-in <code>nextpage</code> retains the current location in the page (in case the page is not displayed entirely) |
| ~PagePrevLink | Create a link with Acrobat's previous page action (displays the <i>top</i> of the previous page) | Link | alert ~PagePrevLink | FrameMaker's built-in <code>previouspage</code> retains the current location in the page (in case the entire page is not displayed) |
| ~ViewNextLink | Create a link to retrace views forward | Link | alert ~ViewNextLink | |
| ~ViewPrevLink | Create a link to retrace steps backward | Link | alert ~ViewPrevLink | |

FrameMaker-to-Acrobat TimeSavers Shortcuts v. 5.0 (inserted in hypertext markers) (6 of 7)

| Shortcut | Function | Item defined | Hypertext marker syntax | Notes |
|-------------------------------|---|-------------------------|---|---|
| Document Settings | | | | |
| ~ViewDoc | Set initial view settings | Doc. setting | alert ~ViewDoc | Global settings can be specified through the PDF Settings tab |
| ~PdxDoc | Associate an Acrobat index with the current document | Doc. setting | alert ~PdxDoc (index) | pdx is automatically appended to file name (can also be set through the PDF Settings tab) |
| ~BaseURLDoc | Set a base URL | Doc. setting | alert ~BaseURLDoc (webaddress) | Web address is prefixed with http:// (can also be set through the PDF Settings tab) |
| Quick Access Bookmarks | | | | |
| ~Bmk | Define a QuickAccess bookmark to a destination within a paragraph | Bookmark | alert ~Bmk (term) /Destination | QuickAccess bookmarks point to destinations within paragraphs; sorted automatically in the distilled PDF; enable the <i>Extract quick-access bookmarks</i> function, Bmk Extraction tab. If the bookmark text does not include punctuation symbols or special characters, it is easier to use the following marker: newlink BMK term |
| ~BmkNote | Define a QuickAccess bookmark to a destination within a paragraph + an Acrobat note | Bookmark + Acrobat note | alert ~BmkNote (term) /Destination (Note Content) /TLCO | |
| Acrobat JavaScript | | | | |
| ~JSLink | Acrobat JavaScript | Link | alert ~JSLink (JavaScript code) | |
| ~JSBmk | | Bookmark | alert ~JSBmk (Bookmark Title) /CS (JavaScript code) | |
| ~JSPage | | Page action | alert ~JSPage (JavaScript code) | |
| Multi-Purpose | | | | |
| ~NamedActLink | Define any Acrobat action using its name | Link | alert ~NamedActLink /ActionName | |
| ~NamedActBmk | | Bookmark | alert ~NamedActBmk (Bookmark Title) /CS /ActionName | |

FrameMaker-to-Acrobat TimeSavers Shortcuts v. 5.0 (inserted in hypertext markers) (7 of 7)

| Shortcut | Function | Item defined | Hypertext marker syntax | Notes |
|-------------------------------|---------------------------------|------------------------|------------------------------|--|
| Page-Related | | | | |
| ~PageLabelRomanFM | Assign page labels | Page label | alert ~PageLabelRomanFM num | Intended use is page labels in a book with roman-numbered front-matter, followed by sequential page numbering, converted to a single PDF. Place this hypertext marker in the first page of the first chapter after front matter pages (page 1). num indicates the number of unnumbered pages which precede the roman section (such as title page). If the first page in the book is numbered <i>i</i> , specify 0. |
| ~PageLabel | Assign page labels | Page label | alert ~PageLabel (text-) | Intended use is page labels in individual documents. For chapter-based prefixes in a single PDF, the PageLabeler plug-in is recommended (see www.frameexpert.com for details). |
| ~PageLabelNum | Assign page labels | Page label | alert ~PageLabel (text-) num | |
| ~PagePlate | Assign a page plate | Page plate | alert ~PagePlate (text) | |
| ~PagePlateC | Assign a “Continued” page plate | “Continued” page plate | alert ~PagePlateC (text) | |
| ~PageRotate | Specify page rotation | | | Works only if Acrobat Distiller’s AutoRotate is not active |
| Event-Related Messages | | | | |
| ~CloseMsg | | Event message | alert ~CloseMsg (text) | |
| ~WillPrintMsg | | Event message | alert ~WillPrintMsg (text) | |
| ~DidPrintMsg | | Event message | alert ~DidPrintMsg (text) | |
| ~WillSaveMsg | | Event message | alert ~WillSaveMsg (text) | |
| ~DidSaveMsg | | Event message | alert ~DidSaveMsg (text) | |